



**CAME**

| **GATE  
OPERATORS**

**FROG**

RESIDENTIAL UNDERGROUND  
SWING GATE OPERATOR



## Invisible Solution for Ornamental Swing Gates



LiftMaster®, the industry leader in gate access systems in North America, has partnered with Italian manufacturer CAME Access Automation. The integration of LiftMaster's Security+ 2.0™ radio technology with CAME's sleek Italian design allows us to offer a complementary line of residential gate operators backed by our unmatched sales and service support.

The Frog Residential Underground Swing Gate Operator is ideal for ornamental swing gates. Installed below grade in a waterproof casing, and protected by a steel access plate that is flush with the driveway surface, it provides an invisible solution.

The Frog offers all the advanced features you demand:

**LiftMaster® Security+ 2.0™ radio technology**  
2x the range of standard remotes

**On-board receiver** provides a single remote solution for gate and garage access

**Ultra-reliable, maintenance-free direct gear drive system;** watertight motor provides unmatched reliability and quiet operation

**24V DC motor** with soft stop moves an 11.5 ft. gate up to 1,770 lbs.

**Adjustable speed control** moves gate with precision

**Simple manual disconnect** for emergency operation

**Timer-to-Close** automatically closes the gate after preset time

**For single and dual gate applications**

**LiftMaster®**



**CAME** | GATE OPERATORS

# FROG

## RESIDENTIAL UNDERGROUND SWING GATE OPERATOR

### Specifications

**Power:** 120V AC, single phase

**Motor power:**  
24V DC continuous duty

**Accessory power output:**  
24V AC, 2 amps

**Receiver:** Security+ 2.0™, holds 50 transmitters, HomeLink® compatible\*

**Surge suppression:** On high and low voltage inputs

**Operator duty cycle rating:**  
25 cycles per day

**Gate travel speed:** 90-degree opening adjustable in 16-45 seconds

**Temperature specifications:**  
-4°F to 131°F (-20°C to 55°C)

**Warranty:**  
3 years for residential applications

\*May require an external adapter depending on the make, model and year of your vehicle. Visit [www.homelink.com](http://www.homelink.com) for additional information.

### Construction

**Cover:** Galvanized steel

**In-ground casing:** Coated steel

**Operator motor casing:**  
Cast aluminum

**Shipping weight:**  
FROG 1PKG Master Kit  
- Motor assembly, underground casing, key release, control box: 78 lbs.

FROG-S: Secondary Kit  
- Motor assembly, underground casing, key release: 62 lbs.

**ETL listed:** ETL-approved and compliant with standards UL-325 for U.S.A. and CSA C22.2 #247 for Canada.

IMPORTANT: To be compliant with UL-325 and industry safety guidelines, qualified secondary entrapment devices such as photo-eyes or sensing edges are required to be installed with this gate operator.

### Add to Your System



**DIR10M:** CAME thru-beam photo-eyes, 32.8' sensing distance, NC contact



**DIRL:** CAME extruded 16.5" aluminum photo-eye mounting post with base



**DIRZ:** CAME photo-eye aluminum alloy impact cover



**LD7LP:** LiftMaster® low-power loop detector



**895MAX:** LiftMaster® 3-button premium Security+ 2.0™ remote control



**890MAX:** LiftMaster® 3-button mini Security+ 2.0™ remote control




**TAC1:** LiftMaster® telephone entry system




**EL25:** LiftMaster® telephone entry system

### Recommended Capacities

#### Swing Rating



### Dimensions



# LiftMaster®

THE CHAMBERLAIN GROUP, INC.  
845 Larch Avenue  
Elmhurst, IL 60126  
[LiftMaster.com/CAME](http://LiftMaster.com/CAME)

LMCMCAFROG  
Printed in U.S.A. 07/12  
©2012 The Chamberlain Group, Inc.



Follow us on Facebook, Twitter and YouTube!

